



A Tenaga Nasional Subsidiary

REQUEST FOR QUOTATION (RFQ) NOTICE

Vendors are invited from suppliers / Tenaga Nasional Berhad (TNB) and/or Allo Technology Sdn. Bhd. (Allo) for supply / work as follows:

Description:	PA SYSTEM FOR ALLO TECHNOLOGY SDN BHD
Category of Works/Supplies:	INFORMATION TECHNOLOGY
Floatation Start Date and Time:	15th November 2023, Wednesday (5.00 p.m.)
Closing Date and Time:	24th November 2023, Thursday (12.00 p.m.)
Submission of documents:	Single envelope submission consists of hardcopy of Quotation, duly completed/signed in accordance with instructions therein, must be submitted not later than 12.00PM on 24 November 2023 and shall be addressed to as follows:

ALLO TECHNOLOGY SDN BHD

Level 3, Left Wing,
College of Computer Science and Information Technology (CSIT), UNITEN,
43000 Kajang, Selangor
(Attn: Head of Procurement & Supply Chain)
(Allo Tender Box)

Please find BOQ below for reference.

Qualifications:	a) Sdn. Bhd. or Enterprise Companies b) Registered with Tenaga Nasional Berhad (TNB) and/or Allo Technology Sdn. Bhd. (Allo)
-----------------	---

A. CONTACT INFORMATION FOR GENERAL ENQUIRIES

Contact Person: Muhammad Izzat Hafiz
Email: procurementallo@allo.my/izzat@allo.my

REQUEST FOR QUOTATION (RFQ) NOTICE

No	Scope of Work	U.O.M	Qty	Price/Unit (RM)	Total (RM)
1	<p>Mixer Amplifier</p> <p>Power Source: 100 - 240 V AC, 50/60Hz Rated Output: 240 W Power Consumption: 62 W Frequency Response: 50 - 20,000 Hz Input: 1. MIC: 1 mV(-60dB), 600 ohm, balanced, phone jack, selectable to RJ45 and AUX 2. AUX: 100 mV(-20dB), 10k ohm, unbalanced and RCA pin jack. MP3: LED Display, Support USB, SD/MMC card, Bluetooth, Radio FM, Record Output: 1. Speaker out: Speaker Output in screw type terminal 2. Direct line: 42 Ω (100 V) or 4 Ω 3. Rec out: 0 dB, 600 Ω, unbalanced, RCA pin jack Total Harmonic Distortion: Under 1% at 1 kHz, 1/3 rated power Indicator: On Power, Signal, Peak, Protect</p>	unit	1		
2	<p>Speaker</p> <p>Enclosure: 2-way bass-reflex type Rated Input: 30 W Rated Impedance: 1. 8 Ω 2. 100 V line: 330 Ω (30 W), 500 Ω (20 W), 670 Ω (15 W), 1 kΩ (10 W), 2 kΩ (5 W) 3. 70 V line: 170 Ω (30 W), 250 Ω (20 W), 330 Ω (15 W), 500 Ω (10 W), 1 kΩ (5 W) Sund Pressure Level: 90 dB (1 W, 1 m) Frequency Response: 80 Hz - 20 kHz Speaker Component: 12 cm cone-type + dome-type Speaker Cord: 2-core cabtyre cord with diameter of 6 mm</p>	unit	4		
3	<p>Wireless Microphone</p> <p>Microphone Element: Dynamic with cardioid pattern RF Carrier Power: 10 mW Audio Frequency Response: 80 - 15,000 Hz Audio Input Level: 140 dB SPL (Maximum) Battery: AA size alkaline battery, 1.5V Battery Life: Approx. 10 hours Indicator: Battery Status LED, 7 Segments LED</p>	unit	2		



A Tenaga Nasional Subsidiary

REQUEST FOR QUOTATION (RFQ) NOTICE

4	Professional Services Installation works for PA system including delivery To undertake painting work for speaker cable casing Accessories for installation (Pipe, casing and etc) Touch up plaster ceiling	unit	1		
SST					
GRAND TOTAL					

Note

1) You may submit your quotation by using this ALLO's form and attached with your company quotation format.

Compliance

Payment Term: Within forty five (45) days upon invoice submission and acceptance by Allo	Yes / No
--	----------

- NOTE:** Please contact Izzat at 017-5012391 for site survey.